


ITEM	QUANTITY	PART NUMBER	DESCRIPTION	
1	1	5874	HOUSING	
2	1	5875	CAGE	
3	1	5877	SCREW TO SPRING ADAPTER	
4	1	5322	POPPET TO SPRING ADAPTER	
5	1	1365	SCREW	
6	1	SELECT SPRING FOR MAX. PRESSURE SETTING		
		MODEL CODE	PT. NO.	MAX. SETTING
		24	5879	2400 PSI
		42	5880	4200 PSI
7	1	1132-8	PLUG, SOCKET- SAE NO. 8	
8	1	5876	POPPET	
9	1	1518-020	O-RING, VITON 75	
10	1	1402-916	O-RING, BUNA 90	
11	1	1518-016	O-RING, VITON 75	
12	2	1221-016	BACK-UP RING, 1/2 WIDTH	
13	2	1100-119	O-RING, BUNA 90	
14	2	1221-119	BACK-UP RING, 1/2 WIDTH	

RDIF2-16X-FR-XX-XX
DIFFERENTIAL RELIEF CARTRIDGE-16 SERIES

GENERAL SPECIFICATIONS	
PRESSURE	4,500 PSI MAXIMUM SETTING.
FLOW RATE	50 GPM AT 100 PSI + SPRING DIFFERENTIAL.
MEDIA	PETROLEUM MINERAL BASE SAE 20. OTHER BASES MAY REQUIRE SEAL CHANGES.
CAVITY	5053-16-2
SEAL KIT	5324
LEAKAGE	INTERNAL-5 CUBIC INCHES/MIN., EXTERNAL-NONE.
SET PRESSURE	DROPS BECOME STREAM



FUNCTIONAL SYMBOL

OMIT IF
NO BODY

