

ITEM	QUANTITY	MODEL CODE	PART NUMBER	DESCRIPTION
1	1	ALL	1404	SCREW
2	1	ALL	1218	HEX NUT
3	1	ALL	1405	CAP, ADJUSTING
4	1	ALL	1089-012	BACK-UP RING
5	1	ALL	1570-012	O-RING, VITON 90 DURO.
6	1	16	1402-908	O-RING, BUNA 90 DURO.
	1	16V	1519-908	O-RING, VITON 90 DURO.
7	1	ALL	5860	HOUSING
8	1	25	5087	SPRING, RELIEF PRESSURE 100-2500 PSI
	1	50	5088	SPRING, RELIEF PRESSURE 200-5000 PSI
9	1	ALL	5578	GUIDE
10	1	ALL	1087-187	BALL, STEEL
11	1	ALL	5859	CAP
12	1	16	1402-916	O-RING, BUNA 90 DURO.
	1	16V	1519-916	O-RING, VITON 90 DURO.
13	1	ALL	1570-115	O-RING, VITON 90 DURO.
14	1	ALL	5419	SPRING
15	1	ALL	5857	CAGE
16	1	ALL	5868	RING, WIRE
17	1	ALL	5858	SPOOL
18	2	ALL	1221-119	BACKUP, 1/2 WIDTH
19	1	16	1100-119	O-RING, BUNA 90 DURO.
	1	16V	1570-119	O-RING, VITON 90 DURO.
20	2	ALL	1221-118	BACKUP, 1/2 WIDTH
21	1	16	1100-118	O-RING, BUNA 90 DURO.
	1	16V	1570-118	O-RING, VITON 90 DURO.
22	2	ALL	1221-117	BACKUP, 1/2 WIDTH
23	1	16	1100-117	O-RING, BUNA 90 DURO.
	1	16V	1570-117	O-RING, VITON 90 DURO.

GENERAL SPECIFICATIONS

PRESSURE	5,000 PSI WORKING
FLOW RATE	40 GPM
MEDIA	PETROLEUM MINERAL BASE SAE 20 OTHER BASES MAY REQUIRE SEAL CHANGES
CAVITY	5053-16-4
SEAL KIT	
LEAKAGE	INTERNAL 10 CUBIC INCHES/MIN., EXTERNAL NONE
FOR 250-450° F	SPECIFY VITON WITH A (10V)

SELECT ITEM 8 FOR
PROPER RELIEF PRESSURE

BLANK FOR BUNA O-RINGS
V FOR VITON O-RINGS

SEQ-16X-A-XX
16 SERIES 4-WAY SEQUENCE CARTRIDGE

